

Informationen zum Produkt



190DH-M

Weitere Füllvolumen


Kleinster Eimer:
155ml



Füllvolumen:	Ø:	Höhe o.D.:	Gewicht Eimer Bügel, Deckel (+/-3%)	IML-Druck Becher	IML- Druck Deckel	Weiteres:
190ml	76mm	67mm	11g / 4g	ja	ja	Siehe Spez.
<ul style="list-style-type: none"> • PP-Spritzgussbecher mit Originalitätsverschluss (Zertifikat Lebensmittelsicherheit) • Standardausführung: klar mit klarem Deckel, klarer Bügel – WEISSER BÜGEL bestellbar (Einfärbung in Standard-/Sonderfarben möglich) 						
Menge je Palette Schalen:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
16.800 St.	1.050 St.	595x395x460mm 850g	130g	1200x800x150mm 12kg	2,20m	Siehe Spez.
Menge je Palette Deckel:	in 12 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
67.200 St.	5.600 St.	595x395x460mm 850g	130g	1200x800x150mm 12kg	2,20m	Siehe Spez.

Technical specification:

Tolerance:
Weight/Volume +/- 5,0%
Dimensions +/- 0,5 mm



	Bucket	Lid
Volume up to edge	210 ml.	
Material/weight	PP/ 11 g	PP/ 4 g
Top dimension D-D1	D 76 mm	D1 74 mm
Bottom dimension Š-Š1	Š 60,5 mm	
Height with lid V	V 67,4 mm	6,5 mm
Number in 1 ct	1050	5600
Number of ct on 1 palette	16	-

Other characteristic

Uses:

containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.

Hot filling:

packaging is suitable for contact with the hot filling (85°C-95°C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before to written approval for use at hot temperatures.

Cold temperatures:

packaging made from the special cold-resistant material can be used at temperatures -20°C. It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before to written approval for use at low temperatures.

Storage:

suitable storage includes protection of direct sun light, rain, very high temperatures over a long period. Packaging must be not more than 2,4m in height and at least 1m away from heat source.

Recommended period of storage – 12 months after delivery to suitable storage.