

## Informationen zum Produkt



## 1150Q-M

**Weitere Füllvolumen SERIE-M:**  
640ml



Füllvolumen:	Maße:	Höhe o.D.:	Gewicht Becher, Deckel (+/-3%)	IML-Druck Becher	IML- Druck Deckel	Weiteres:
1150ml	128x128mm	112mm	37g / 9g	nein	ja	Siehe Spez.
<ul style="list-style-type: none"> <li>• PP-Spritzgussbecher mit Originalitätsverschluss (Zertifikat Lebensmittelsicherheit)</li> <li>• Standardausführung: klar mit klarem Deckel (Einfärbung in Standard-/Sonderfarben möglich)</li> </ul>						
Menge je Palette Schalen:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
4.640 St.	290 St.	580x400x500mm 650g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.
Menge je Palette Deckel:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
27.840 St.	1.740 St.	580x400x500mm 650g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.

### Technical specification:

Tolerance:  
Weight/Volume +/- 5,0%  
Dimensions +/- 0,5 mm



	Container	Lid
Volume up to the edge	1150ml.	
Material/weight	PP/ 37 g	PP/ 9g
Top dimension D-D1	D 128,5x128,5 mm	D1 125,5x125,5 mm
Bottom dimension Š-Š1	Š 102,3x102,3mm	
Height V	V 112,4 mm	8,2mm
Number in 1 ct	290	1740
Number of ct on 1 palett	16	16

### Other characteristic

#### Uses:

containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.

Hot filling:

packaging is suitable for contact with the hot filling (85°C-95°C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before to written approval for use at hot temperatures.

Cold temperatures:

packaging made from the special cold-resistant material can be used at temperatures -20°C. It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before to written approval for use at low temperatures.

Storage:

suitable storage includes protection of direct sun light, rain, very high temperatures over a long period. Packaging must be not more than 2,4m in height and at least 1m away from heat source.

Recommended period of storage – 12 months after delivery to suitable storage.