

## Informationen zum Produkt



## 2300REDH-M

### Weitere Füllvolumen SERIE-M:

1250ml ohne Bügel  
1750ml ohne Bügel  
2300ml ohne Bügel



Füllvolumen:	Maße:	Höhe o.D.:	Gewicht Eimer (ohne Bügel), Deckel (+/- 3%)	IML-Druck Becher	IML- Druck Deckel	Weiteres:
2300ml	200x135mm	122mm	62g / 17g	nein	ja	Siehe Spez.
<ul style="list-style-type: none"> <li>• PP-Spritzgusseimer mit Originalitätsverschluss (Zertifikat Lebensmittelsicherheit)</li> <li>• Standardausführung: klar mit klarem Deckel (Einfärbung in Standard-/Sonderfarben möglich)</li> </ul>						
Menge je Palette Schalen:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
3.072 St.	192 St.	580x400x500mm 650g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.
Menge je Palette Deckel:	in 16 Boxen gepackt je:	Maß/Gewicht je Umkarton	Gewicht je Folienbag	Maß/Gewicht Einweg-Palette	Pal-Höhe	Weiteres:
15.360 St.	960 St.	580x400x500mm 650g	120g	1200x800x150mm 12kg	2,20m	Siehe Spez.

Technical specification:

Tolerance:  
 Weight/volume +/- 5,0%  
 Dimensions +/- 0,5 mm



	Container	Lid
Volume up to the edge	2300ml.	
Material/weight	PP /62 g	PP/ 17g
Top dimension D-D1	D 135x200 mm	D1 135x200
Bottom dimension Š-Š1	Š 108x122mm	
Height V	V 122 mm	8,5mm
Number in 1 ct	192	960
Number of ct on 1 palett	16	16

Other characteristic

Uses:

containers with lids are intended for direct contact with watery, acidic, fat food products, which temperature is room and lower.

**Hot filling:**

packaging is suitable for contact with the hot filling (85°C-95°C) and short-term use in the microwave. Packaging must be tested by the customer with the actual product before to written approval for use at hot temperatures.

**Cold temperatures:**

packaging made from the special cold-resistant material can be used at temperatures -20°C. It is produced according to customer requirements. Packaging must be tested by the customer with the actual product before to written approval for use at low temperatures.

**Storage:**

suitable storage includes protection of direct sun light, rain, very high temperatures over a long period. Packaging must be not more than 2,4m in height and at least 1m away from heat source.

Recommended period of storage – 12 months after delivery to suitable storage.